



EM730 MULTIMETER

SPECIFICATION SHEET

DISPLAY TYPE	BACKLIT LCD
TRUE RMS	Yes
AC VOLTAGE	4V-40V-400V-1000V
DC VOLTAGE	400mV-4V-40V-400V-1000V
AC/DC CURRENT PROBE	-
AC CURRENT	400 μ A-4000 μ A-40mA-400mA-4A-10A
DC CURRENT	400 μ A-4000 μ A-40mA-400mA-4A-10A
RESISTANCE	400 Ω -4k Ω -40k Ω -400k Ω -4M Ω -40M Ω
FREQUENCY	9.999Hz-99.99Hz-999.9Hz-9.999kHz-99.99kHz-999.9kHz-9.999MHz
RPM IP	-
RPM IG	-
DUTY CYCLE	-
PULSE WIDTH	-
DWELL ANGLE	-
TEMPERATURE	-4°F to 1832°F (-20°C - 1000°C)
CAPACITANCE	40nF-400nF-4 μ F-40 μ F-400 μ F-4000 μ F
MAX/MIN AVG RECORDING	-
BACKLIGHT LCD	Yes (Positive LCD, 80mm*54mm)
BLUETOOTH	-
USB	-
SAFETY STANDARD	CAT III 1000V/CATIV 600V
3 YEAR REPLACEMENT WARRANTY	Yes

